

# Active Sub Compact / Technical datasheet



## We have the power

This active subwoofer was specially featured by ML for bending wave transducers and can thus be combined to optimum effect with Novasonar flat-panel loudspeakers. The Active-Sub Compact can be used wherever either technical or visual sophistication is required and is a suitable component in numerous applications.

### A & E Specifications

#### Description:

Active subwoofer with crossover and volume control.

Active 200-mm sub-bass, bass-reflex casing, integrated amplifier with active crossover. Black housing, varnished.

Dimensions: 420 mm x 275 mm x 430 mm

Frequency range: 30 Hz to 300 Hz

Adjustment range: 40 Hz to 180 Hz

Power handling: 55 W / 8 ohms

Sensitivity: 84 dB (1 W / 1 m)

Max. SPL: 101 dB (1 m)

Manufacturer: ML Audio+Carbons  
Model: Active Sub Compact

<b>DIMENSIONS (HxWxD)</b>	420 mm x 275mm x 430 mm
<b>WEIGHT</b>	12,2 kg
<b>FREQUENCY RANGE</b>	30 Hz – 300 Hz
<b>POWER HANDLING</b>	55 watts RMS
<b>SENSITIVITY</b>	84 dB 1 watt / 1 metre
<b>CROSSOVER</b>	40 Hz – 180 Hz
<b>IMPEDANCE</b>	8 ohms

All products subject to technical modification without prior notice. Errors excepted

ML Audio + Carbons GmbH Lautsprechertechnik - Ulmenstraße 15 - D-65428 Rüsselsheim  
Tel. +49-(0)700-93735565 or +49-(0)163-5306360 - Fax +49-(0)6131-6030796  
E-Mail: info@mllaudio.de - Web: www.mllaudio.de